



Pellon Projects™



Find more information and free downloadable projects at www.PellonProjects.com

SUPPLIES & TOOLS:

- ½ yard main fabric
- ½ yard lining fabric
- 1 yard Pellon® 809 Décor-Bond®
- Thread

- Sewing machine and related supplies
- Iron and ironing board
- Rotary cutter and related supplies

DIRECTIONS: FINISHED SIZE IS 8½L X 9"W X 7"H.

- 1. Cut one 18" x 24" rectangle each of main fabric and lining fabric. Cut two 18" x 24" rectangles of Décor-Bond®.
- 2. Place the main fabric wrong side up on ironing board. Smooth wrinkles. Place one rectangle of Décor-Bond® with the fusible side facing down on the main fabric.
- Fuse following manufacturer's instructions. Repeat steps 2 and 3 with the lining fabric and remaining rectangle of Décor-Bond®.
- 4. Fold the 18" x 24" rectangle of main fabric in half with right sides together so it measures 18" x 12". Pin at sides. Stitch both side seams using a ½" seam allowance. Repeat step with rectangle of lining fabric.
- 5. Press the side seams just sewn with the seam allowances still facing each other. Then open side seams and press again.
- 6. Turn the main fabric so side seams are lying flat and facing upwards. Make a point, so there is a 45° seam along the side. Finger press.
- 7. Measure 4" in from the point and mark a line. Repeat for other corner. Pin along lines. Repeat steps 5, 6 and 7 with the lining.
- 8. Stitch along lines. Backstitch at each end. Cut off the points, leaving a ½" seam allowance.
- 9. Open both pieces so the bottoms are flat and they sit like bins. Main fabric should be wrong side out and lining fabric right side out. Place the lining bin inside the main fabric bin. Align all corners and side seams. Pin in place at bottom corners. Pin around top edge.
- 10. Stitch around the top using a ½" seam allowance. Leave a 4" opening near a side seam.
- 11. Pull the main fabric right side out through the 4" opening.
- 12. Place the bin so the top edge lies flat with seam allowance toward main fabric. Press top edge. This will help create a crisp edge when pushing the lining down into the main fabric. Turn in the 4" opening and press. Pin to hold.
- 13. Push the lining bin down inside the main fabric bin, aligning the top edge so it is flat.
- 14. Press entire top edge. Edgestitch along the top edge, backstitching at the end.

For detailed project instructions visit www.PellonProjects.com.